

[CONTACT US](#) ▶

[DESCRIPTION](#) ▶

[TAC-PAVE](#) ▶

[TEST RESULTS](#) ▶

[IDEAL USES](#) ▶

[APPLICATION](#) ▶

[QUESTIONS](#) ▶

[SPECIFICATIONS](#) ▶

[TESTIMONIALS](#) ▶

[BROCHURE \(pdf\)](#) ▶

[HOME](#) ▶

Glow Line is applied to new or existing work. Previously painted surfaces shall be prepared by grinding or water blasting prior to the application of Glow Line. It is tolerant to a wide range of humidity and temperature conditions.

Glow Line is mixed on site and applied using a textured paint roller or spray. Glass beads are then applied, under pressure onto the wet material.

Full cure is normally obtained within 30 minutes at 20 degrees celsius and average humidity.

CONTACT DETAILS:

WESTERN ROADS & TAC-PAVE
POST OFFICE
BUSHY PARK
TASMANIA 7140
EMAIL billbantton@glowline.info

WITHIN AUSTRALIA:

Telephone: (03) 62861195
Toll Free: 1800 822 728
Fax: (03) 62862066
Mobile: 0418952234

FROM OVERSEAS:

Telephone: 61 3 62861195
Fax: 61 3 62862066
Mobile: 61 418952234

ZOOM IN ON THE
IMAGES BELOW
BY CLICKING
ON THEM



Website designed and produced by:
[Travel Australia - Internet](#)